

Specification:

Sh.Thickness											
M.S		S.S									
Shearing length mm	Nominal rake angle	Maximum rake angle	Nominal rake angle	Maximum rake angle	Rake angle	Rake angle range	Stroke/minute at.min & max.rake angle	Holddowns	Holding Forces Kgs	Power HP	Material
2500	3.15	4	2	3	1°15'	0.5-2°	2/8-13	13	2500	5	3
3000	3.15	4	2	3	1°15'	0.5-2°	26-9	15	2500	5	3
1500	4	6	3	4	1°37'	0.5-3°	30-15	8	4500	7.5	
2000	4	6	3	4	1°37'	0.5-3°	28-13	11	6200	7.5	
2500	4	6	3	4	1°37'	0.5-3°	30-80	13	8000	7.5	
3000	4	6	3	4	1°37'	0.5-3°	28-80	15	10000	10	
4000	4	6	3	4	1°37'	0.5-3°	22-80	20	12000	10	
1500	6	8	4	6	1°45'	0.5-3°	24-80	8	6500	10	
2000	6	8	4	6	1°45'	0.5-3°	22-70	11	6500	10	
2500	6	8	4	6	1°45'	0.5-3°	28-80	13	8500	15	

3000	6	8	4	6	1°45'	0.5-3°	24-60	15	10800	15	
4000	6	8	4	6	1°45'	0.5-3°	24-60	20	13600	20	
1500	8	10	6	8	2°	0.5-3°	20-10	8	10500	15	
2000	8	10	6	8	2°	0.5-3°	18-80	11	12000	15	
2500	8	10	6	8	2°	0.5-3°	24-80	132	16500	20	
3000	8	10	6	8	2°	0.5-3°	20-60	15	18500	20	
4000	8	10	6	8	2°	0.5-3°	20-80	20	23000	30	
1500	10	13	8	10	2°	0.5-3°	20-10	8	10500	15	
2000	10	13	8	10	2°	0.5-3°	18-80	11	13000	15	
2500	10	13	8	10	2°	0.5-3°	24-80	13	17500	20	
3000	10	13	8	10	2°	0.5-3°	20-60	15	20000	20	
4000	10	13	8	10	2°	0.5-3°	18-60	20	25000	30	

